GNS CERAMICS
EXCLUSIVELY WHOLESALE



EMIRA



Emira brings the understated beauty of natural stone into a versatile porcelain collection designed for modern interiors and outdoor spaces. Featuring a soft stone aesthetic with gentle tonal movement and subtle surface detail, the range creates a calm, refined foundation without appearing overly busy or heavily patterned.

Available in Warm White and Beige, Emira's two neutral shades have been selected for their easy coordination with timber, cabinetry, feature tiles, and a wide variety of interior finishes. Warm White offers a fresh, softly balanced look, while Beige introduces a natural warmth that works beautifully within earthy and contemporary palettes.

Produced in a practical 600x600mm format with a soft matt P4 finish, Emira combines an inviting tactile appearance with the added slip resistance required for many residential applications. Suitable for floors and walls throughout the home, including bathrooms, laundries, kitchens, living areas, and numerous outdoor spaces such as patios, pool surrounds, alfresco areas and covered entertaining settings.

Emira is an adaptable collection that delivers the natural character of stone in an easy-to-use porcelain surface, allowing a cohesive look to flow from indoor living spaces through to the outdoors.

GNS CERAMICS
EXCLUSIVELY WHOLESALE



White



Beige

600x600mm
Matt P4













GNS Ceramics recommends that our retail shops pass on the following information to the installer and end-user.

Click or Scan for Installation Instructions


Ceramic tiles are only one component of a much larger building system. It is our experience that failure of any tiling system is very often the result of a combination of factors. For example; inappropriate design, type of substrate, surface preparation, temperature during installation, adhesives, incompatibility of products, product failure, environmental factors skill and knowledge of the installers etc; the latter being supplied or controlled by a variety of manufacturers and tradesmen. GNS Ceramics has no involvement in the design, selling and installation processes and once goods have been dispatched from our warehouse we have no control over where and how these products are used. As a result the project manager, and or the tiler are the only people in a position to ensure that all the components used in a project are compatible and that the product is installed in accordance with the Australian Building Code and the Australian Standards.

Installation Instructions for all types of tiles can be found in the GNS Ceramics Price List, and on our website. We suggest these are followed at all times.

Cleaning and Maintenance

Do not use abrasive cleaners and chemicals which could permanently scratch and damage the surface of the tile. For daily cleaning we recommend the use of a mild PH Neutral detergent. Should a more vigorous cleaning programme be required we recommend the use of a proprietary tile cleaner from a specialty tile supplier.

Colour & Pattern Variation Guide



Uniform Appearance | Slight Variation | Moderate Variation | High Variation

Slip Resistance

The best way to minimise the risk of slipping is through safe design principals. This involves a risk management approach which evaluates the likelihood and consequence of an incident to occur. Slip resistive flooring is only one of the design components to consider, other design features should also be considered, including awnings, airlocks, matting and a suitable cleaning regime to reduce the extent of contaminates. Visual aids, warning signs, handrails and lighting, along with the footwear to be worn, should also be considered.

All ceramic tiles can be slippery, particularly when wet. This includes tiles, commonly used in wet areas such as bathrooms. It is important that customers be aware of the potential danger of wet ceramic tiles and seek advice from the retailer as to the level of slip-resistance of any particular tile, and its suitability for the intended application. If there is any doubt, tiles should be tested for slip-resistance immediately after being laid, under the conditions that they will be subject to during use. While tiles may achieve an acceptable standard in a laboratory test, it is quite probable that the performance in-situ will be less than expected, due to installation methods, wear & tear, cleaning regimes and unforeseen circumstances. Test results should therefore to be seen as a relative guide to estimate the merits of one tile versus another and should be used in conjunction with the Australian Building Code and the relevant Australian Standards. Further information on slip resistance is provided in the Australian Standards HB198:2014 - An Introductory guide to the slip resistance of pedestrian surface materials.

There are many factors beyond the control of the supplier that can affect the level of slip-resistance of tiles, or contribute to the incidents of injury through slipping. Consequently, the laboratory test results presented here must not be viewed to mean that GNS Ceramics Pty Ltd, is providing any warranty, nor will accept any liability for personal injury or accidents arising from the selection or installation of tiles under any circumstances.

Classes of Use

The classification has taken into account the recommendations of the Australian Standards; however, they are given for general guidance only. They are valid for the given application under **NORMAL CONDITIONS** and should not be taken to provide accurate product specifications for specific requirements.

WARNING: Other standards and building code requirements may affect your selection of tiles.

Consideration should be given to the footwear, type of pedestrian traffic and cleaning methods expected. Floors should be adequately protected against soiling from following trades during installation; they should also be protected against scratching dirt at the entrances to building by interposing footwear cleaning devices. For example, mats, shoe scrapers, static devices, etc.

CLASS 4 - Floor coverings that are walked on by regular traffic with some scratching dirt so that conditions are more severe than CLASS 3; For example, entrances, laundries with external access, living areas, entertainment areas, patio's, sales rooms, motels.

GREEN TAG CERT TM | GreenRate | Level A

GLOBAL GREEN TAG CERTIFIED

CERT TM

GreenRate | Level A

trust brands™

Foshan Padua Ceramics Co., Ltd

Room 1101, Building T13, Smart New City, Jihua 1st Road, Chancheng District, Guangdong, China

This is to Certify that the following Product/s have been found in conformance with the Global GreenTag CertTM Scheme Standard for the Tier and Level noted herein:

Porcelain Tiles

GreenRate Level A

Licenced Sites:
Fujian, China
Licence No.:
FMM:FJ01:2026:GR
Licence Date:
29 June 2026
Latest Revision Date:
29 June 2026
Valid to:
29 June 2027
GreenTag CERT TM Standard:
Standard Version 4.1

GLOBAL GREEN TAG
green product certification
trust brands
www.globalgreentag.com

David Baggs
Global GreenTag Cert TM Chief Executive Officer

GLOBAL GREEN TAG®

green product certification
trust brands

Conditions of Licence

The conditions of licence are contained in full in the Global GreenTag[CERT TM] Standard, Terms and Conditions, and Rules for the Use of the Mark Documents as sighted and/or executed by the Licensee.

In summary it is the responsibility of the licensee in particular to:

1. always comply with the relevant provisions of the GreenTag certification program;
2. make all necessary arrangements for the conduct of the future evaluation, including provision for examining documentation and access to all areas, records (including internal audit reports) and personnel for the purposes of evaluation (e.g. testing, inspection, assessment surveillance, reassessment) and resolution of complaints;
3. make claims regarding certification only in respect of the scope for which certification has been granted;
4. not use its product certification in such a manner as to bring the GreenTag into disrepute and not make any statement regarding its product certification which the certification body may consider misleading or unauthorized;
5. upon suspension or cancellation of certification, discontinue its use of all advertising matter that contains any reference thereto and returns any certification documents as required by GreenTag;
6. use certification only to indicate that products are certified as being in conformity with specified GreenTag standards;
7. endeavour to ensure that no certificate or report nor any part thereof is used in a misleading manner;
8. make comment or inclusions solely in accordance with license requirements in making reference to its product certification in communication media such as online, emails, documents, brochures or advertising;
9. Inform GreenTag of any change in the Certified product or manufacturing process that is likely to significantly affect the product's design or specification, or changes in the ownership, structure or management of the Licensee, if relevant, or any other information that indicates the product may no longer comply with the requirements of this Standard;
10. In the event of GreenTag determining changes have been made to product or supplier details and not notified to GreenTag, the Licensee will, on receipt of a GreenTag 'Notice to Rectify', immediately provide GreenTag with the required details and any fees necessary to allow recertification. Failure to do so may result in the withdrawal of the Licence. If the product Licence is withdrawn, the Licensee must, within 7 days, cease to further promulgate all product marketing, packaging, advertising or other material carrying the logo. Furthermore all material carrying the Certification Mark/s must be withdrawn within 90 days.

Revision Date	Certificate Number	Notes
29 June 2026	FMM:FJ01:2026:GR	Product certified to GreenTag Standard v4.1

中国认可
国际互认
检测
TESTING
CNAS L1978

国家建筑卫生陶瓷检测重点实验室
STATE KEY TESTING LABORATORY OF BUILDING CERAMICS AND SANITARY WARE
佛山海关综合技术中心
COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN CUSTOMS

检 测 报 告
TEST REPORT

报告编号:
Test report No.: **2520261893**

委托单位: 佛山市美狮马乐建材科技有限公司
Applicant: FOSHAN PADUA CERAMICS CO., LTD.

委托单位地址: 广东省佛山市禅城区智慧一路智慧新城 T13 栋 1102
Address of Applicant: 1102, BLDG T13, SMART CITY, NO.1, ZHIHUI RD., CHANCHENG FOSHAN, GUANGDONG, CHINA

样品名称: 有釉砖
Name of Sample: GLAZED PORCELAIN TILE

样品记号: PD6391
Mark of Samples:

样品规格: 300mm×300mm
Sizes of Sample:

样品来源: 委托单位自送样品
Source of Samples: Samples selected by applicant

样品数量: 5 片
Quantity of Samples: 5 Pieces

接样日期: 2026-08-17
Received on:

检测日期: 2026-08-18
Test Date:

检测依据:
Test Standard: AS 4586-2013/Amdt 1-2017 *Slip resistance classification of new pedestrian surface materials*

检测结果:
Test Results:

检测项目 Test Item	检测方法 Test Method	检测结果 Test Results
防滑性能，摆锤法，湿法，Slider 96 **Slip resistance**, Wet pendulum test method, Slider 96	AS 4586-2013/Amdt 1-2017 Appendix A **附录** A	SRV: 50 **类别** Class: P4

*** ***

报告结束 End of Test Report

检测单位盖章
Stamp of test unit

COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN CUSTOMS (6) 佛山海关综合技术中心 检验检测专用章

授权签字人: 肖景红
Authorized Signatory XIAO JINGHONG

日期: 2026-08-20
Date

声明：1、我们已尽所知所能实施上述检测，不能因签发本报告而免除有关各方根据合同和法律所承担的责任和义务；2、未经本实验室书面许可，不得部分复制本报告；3、本报告仅是样品的检测结果；4、本报告所述的样品信息为委托单位自行声明，实验室不负责其真实性。
Notes: 1. All tests are carried out conscientiously to the best of our knowledge and ability. This report does not in any respect absolve the other related parties from his contractual and legal obligations. 2. This report shall not be reproduced, except in full, without the prior written approval from the issuing laboratory. 3. The results in this report apply to the samples only. 4.The product information is declared by applicant, and laboratory is not responsible for the authenticity.

广东省佛山市禅城区魁奇一路澜石（国际）金属交易中心十八座二楼 2/F, Building 18, Lanshi International Metal Exchange Center, Kuiqiyi Road, Chancheng District, Foshan, Guangdong, China 528000
Tel: 86-0757-83827991 E-mail: fsiqtc@163.com